

**JACOBSEN**<sup>®</sup>



## **ZT1000**

**PROFESSIONAL PERFORMANCE.  
CUT AFTER CUT.**

**UP TO 35HP**  
ENGINE

**UP TO 72"**  
CUTTING WIDTH

**UP TO  
14MPH**

**UP TO 5-YEAR  
WARRANTY**

The Jacobsen ZT1000 series is the flagship of commercial zero-turn mowers in the product line. These new mowers deliver the power, performance, and comfort professionals demand every day. The ZT1000 models come equipped with engines up to 35 horsepower from Kawasaki<sup>®</sup> FX and fuel efficient gas or LP options from Kohler<sup>®</sup> EFI to power through the most demanding properties. The ZT1000 features Suspension Forks and an all-new ISO mounted platform suspension seat with padded armrests, recline, and lumbar for superior operator comfort. Enjoy an incredibly smooth driving experience with Parker<sup>®</sup> HTG transmissions with speeds up to 14 miles per hour and service intervals of 1,000 hours. Demo the ZT1000 today to experience professional performance cut after cut.



Gas



LP

# JACOBSEN® ZT1000

	60-inch Deck			66-inch Deck		72-inch Deck			
Model	3160KW	3160KOE	2960KOELP	3566KW	3366KOE	3572KW	3372KOE	2972KOELP	
<b>Engine</b>									
Manufacturer	Kawasaki® FX	Kohler® Command EFI	Kohler® Command LP EFI	Kawasaki® FX	Kohler® Command EFI	Kawasaki® FX	Kohler® Command EFI	Kohler® Command LP EFI	
Horsepower	31	31	29	35	33	35	33	29	
Displacement	999cc	824cc		999cc	824cc	999cc	824cc		
Air-cleaner	2 stage								
Cooling	Air cooled								
Starter	Electric								
Engine warranty	3 Year								
<b>Drive System</b>									
Dual hydrostatic	Parker® HTG (16cc)								
Ground speed	14 mph								
Parking brake	Integrated in transaxle								
Towing capacity	1000 lbs								
<b>Mower Deck</b>									
Deck size	60"			66"		72"			
Acres/hour	6.7			7.4		8.1			
Cutting height	1" - 5"								
OCDC (operator controlled discharge chute)	Foot-operated (optional)								
Deck height adjustments	Manual lift, 1/4" increments								
Electric lift	Optional								
Deck engagement	Ogura® 250 ft-lbs with SoftStart								
Construction	7 ga formed & welded								
Blades	(3) - 2.5" x 20.5"			(3) - 2.5" 22.5"		(3) - 2.5" 24.5"			
Blade tip speed (approximate)	18,506 fpm			18,518 fpm		18,479 fpm			
Spindles	1" effective diameter machined shaft								
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)								
Anti-scalp rollers	4								
Pulleys	7 ga steel deep groove								
<b>General</b>									
Battery	12 Volt, 350cca								
Digital display	InCommand™ Console - Tachometer, hour meter, blade timer, fuel gauge, and ignition								
Fuel capacity	12								
Rear tires	25 x 12-12 GrassMaster								
Front tires	15 x 6-8								
Frame	Welded C-channel, 7 ga formed								
Floor-pan	Removable, steel								
Seat	High-back, full suspension, lumbar, recline, padded armrest and ISO mounted platform								
Suspension Forks	Standard								
<b>Dimensions</b>									
Overall height (rollbar down)	52.7"								
Overall height (rollbar up)	77.7"								
Overall width (chute down)	76.9"			83.2"		89.5"			
Overall width (chute up)	66.1"			72.5"		78.7"			
Overall length (rollbar down)	90.9"						94.9"		
Overall length (rollbar up)	87.1"						91"		
Weight	1386 lbs	1378 lbs	1434 lbs	1409 lbs	1403 lbs	1426 lbs	1442 lbs	1498 lbs	

\*Acres/hour at top speed and 80% efficient

Engine horsepower is provided by engine manufacturer. Actual operating power output may vary due to conditions of specific use.

NOTE: Specifications, while correct at time of printing, may change without notice.

